




**Ecovision Mini
wall washer**



With high performance LEDs,
integral temperature monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP65 , IK10
housing made of extruded aluminium and
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
polycarbonate cover, silicon gasket,
closure by 4 stainless steel screws,
mounting flange: 2 drilled holes Ø 6.5 mm,
spacing 282 mm, tilt range 120°,
PG11 cable gland, integral driver (AC/DC)

Ecovision Mini, wall washer

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 706 046 009	black	2.3 kg	6 x LED 2.5 W (15 W) warm white (3000 K)	1171 lm	C 0 – 180	C 90 – 270
8 706 066 009	white				15°	103°
8 706 056 009	silver grey					



Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 706 045 009	black	2.3 kg	6 x LED 2.5 W (15 W) neutral white (4000 K)	1253 lm	C 0 – 180	C 90 – 270
8 706 065 009	white				15°	103°
8 706 055 009	silver grey					



Part number*	Description
. 1..	Dimmable luminaire (DALI)
. 2..	Dimmable luminaire (1-10 V)






* Luminaires with two cable glands available upon request

LED (see page 247)
Luminaires available in 2700 K and other colour temperatures upon request



Ecovision Mini wall washer with wall arms

With high performance LEDs,
integral temperature monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP65 , IK10
housing made of extruded aluminium and
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
polycarbonate cover, silicon gasket,
closure by 4 stainless steel screws,
wall arms: 2 drilled holes $\varnothing$ 6.5 mm,
spacing 282 mm, tilt range 310°,
PG11 cable gland, integral driver (AC/DC)



Ecovision Mini, wall washer with wall arms

Part number*	Colour	Weight	Leuchtmittel	Luminous flux	Beam angle γ (FWHM)	
8 706 146 009	black	2.8 kg	6 x LED 2.5 W (15 W) warm white (3000 K)	1171 lm	C 0 – 180	C 90 – 270
8 706 166 009	white				15°	103°
8 706 156 009	silver grey					

Part number*	Colour	Weight	Leuchtmittel	Luminous flux	Beam angle γ (FWHM)	
8 706 145 009	black	2.8 kg	6 x LED 2.5 W (15 W) neutral white (4000 K)	1253 lm	C 0 – 180	C 90 – 270
8 706 165 009	white				15°	103°
8 706 155 009	silver grey					


Part number*	Description
... 1 ..	Dimmable luminaire (DALI)
... 2 ..	Dimmable luminaire (1-10 V)

* Luminaires with two cable glands available upon request

LED (see page 247)

Luminaires available in 2700 K and other colour temperatures upon request







**Ecovision
wall washer**



With high performance LEDs,
integral temperature monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP65 , IK10
housing made of extruded aluminium and
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
polycarbonate cover, silicon gasket,
closure by 4 stainless steel screws,
mounting flange: 2 drilled holes Ø 6.5 mm,
spacing 422 mm, tilt range 120°,
PG11 cable gland, integral driver (AC/DC)

Ecovision, wall washer

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 707 046 009	black	2.9 kg	12 x LED 2.4 W	2238 lm	C 0 – 180	C 90 – 270
8 707 066 009	white		(29 W)		15°	103°
8 707 056 009	silver grey		warm white (3000 K)			



Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 707 045 009	black	2.9 kg	12 x LED 2.4 W	2395 lm	C 0 – 180	C 90 – 270
8 707 065 009	white		(29 W)		15°	103°
8 707 055 009	silver grey		neutral white (4000 K)			



Part number*	Description
1..	Dimmable luminaire (DALI)
2..	Dimmable luminaire (1-10 V)

* Luminaires with two cable glands available upon request






LED (see page 247)
Luminaires available in 2700 K and other colour temperatures upon request



Ecovision

wall washer with wall arms

With high performance LEDs,
integral temperature monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP65 , IK10
housing made of extruded aluminium and
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
polycarbonate cover, silicon gasket,
closure by 4 stainless steel screws,
wall arms: 2 drilled holes Ø 6.5 mm,
spacing 422 mm, tilt range 310°,
PG11 cable gland, integral driver (AC/DC)



Ecovision, wall washer with wall arms

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 707 146 009	black	3.4 kg	12 x LED 2.4 W (29 W) warm white (3000 K)	2238 lm	C 0 – 180	C 90 – 270
8 707 166 009	white				15°	103°
8 707 156 009	silver grey					

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 707 145 009	black	3.4 kg	12 x LED 2.4 W (29 W) neutral white (4000 K)	2395 lm	C 0 – 180	C 90 – 270
8 707 165 009	white				15°	103°
8 707 155 009	silver grey					

Part number*	Description
... 1 ..	Dimmable luminaire (DALI)
... 2 ..	Dimmable luminaire (1-10 V)

* Luminaires with two cable glands available upon request

LED (see page 247)

Luminaires available in 2700 K and other colour temperatures upon request

